



DECLARATION OF PERFORMANCE
in accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)
amended by Commission Delegated Regulation (EU) No 574/2014

No 40038

Unique identification code of the product type: **40038 ARDEX X5T Gray, EN 12004:C2TE**

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Improved cementitious adhesive with reduced slip and
extended open time for internal and external tiling**

Name, registered trade name or registered trade mark and contact address of the manufacturer:

ARDEX Yapı Malzemeleri Ltd. Sti.
Istanbul Deri Organize Sanayi Bölgesi
Desen Sokak No: 14/A C-1 Özel Parsel
34956 Tuzla/Istanbul
Türkiye

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
Reaction to fire: System 4

Harmonised standard: **EN 12004:2007+A1:2012**

Notified body:



LGAI TECHNOLOGICAL CENTER, S. A./Applus identification number **0370**

Declared Performance:

Essential Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
Reaction to fire:	E	System 4	EN 12004:2007+A1:2012
Bond strength			
Initial tensile adhesion strength:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Durability of bond strength			
Tensile adhesion strength after heat ageing:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after water immersion:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Tensile adhesion strength after freeze-thaw cycles:	≥ 1.0 N/mm ²	System 3	EN 12004:2007+A1:2012
Release of dangerous substances:	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ARDEX GmbH
 Friedrich-Ebert-Str. 45
 58453 Witten

Arnd Haase
 Deputy Director R &D

Bernd Unterbrink
 R & D Section Head

Witten, 18th October 2024

(Place and date of issue)

Additional Product Characteristics

Additional Characteristics	Performance	System for assessing and reviewing performance consistency	Harmonised Technical Specification
Special Characteristics			
Open time:	≥ 0.5 N/mm ² after not less than 30 minutes	System 3	EN 12004:2007+A1:2012
Slip:	≤ 0.5 mm	System 3	EN 12004:2007+A1:2012