

## DECLARATION OF PERFORMANCE in accordance with Annex III of Regulation (EU) No 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No 574/2014

No 40035

Unique identification code of the product type: 40035 ARDEX X3T-W, EN 12004:C1T

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

## Normal setting cementitious adhesive with reduced slip for internal and external tiling

Name, registered trade name or registered trade mark and contact address of the manufacturer:

ARDEX Yapi Malzemeleri Ltd. Sti. Istanbul Deri Organize Sanayi Bölgesi Desen Sokak No: 14/A C-1 Özel Parsel 34956 Tuzla/Istanbul Türkiye

System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3
Reaction to fire: System 4

Harmonised standard:

EN 12004:2007+A1:2012

Notified body:

TEBAR Test Belgelendirme Araştırma Ve Geliştirme Ticaret A.Ş. identification number 2164

ARDEX X3T-W

Issued: 18<sup>th</sup> October2024

## Declared Performance:

| Essential Characteristics                           | Performance | System for assessing and reviewing performance consistency | Harmonised Technical Specification |  |
|---|-------------|--|------------------------------------|--|
| Reaction to fire:                                   | Е           | System 4   | EN 12004:2007+A1:2012              |  |
| Bond strength                                       |             |  |                                    |  |
| Initial tensile adhesion strength:                  | ≥ 0.5 N/mm² | System 3   | EN 12004:2007+A1:2012              |  |
| Durability of bond strength                         |             |  |                                    |  |
| Tensile adhesion strength after heat ageing:        | ≥ 0.5 N/mm² | System 3   | EN 12004:2007+A1:2012              |  |
| Tensile adhesion strength after water immersion:    | ≥ 0.5 N/mm² | System 3   | EN 12004:2007+A1:2012              |  |
| Tensile adhesion strength after freeze-thaw cycles: | ≥ 0.5 N/mm² | System 3   | EN 12004:2007+A1:2012              |  |
| Release of dangerous substances:                    | NPD         |  |                                    |  |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**ARDEX GmbH** 

Friedrich-Ebert-Str. 48

58453 Witter

Bernd Unterbrink R & D Section Head

Deputy Director R &D

Arnd Haase

Witten, 18th October 2024

(Place and date of issue)

## **Additional Product Characteristics**

| Additional Characteristics | Performance | System for assessing and reviewing performance consistency | Harmonised Technical Specification |
|----------------------------|-------------|--|------------------------------------|
| Slip:                      | ≤ 0.5 mm    | System 3   | EN 12004:2007+A1:2012              |

ARDEX X3T-W